According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878

#### SAFETY DATA SHEET

# 2G Adhesive Sealer

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

## 1.1. Product identifier

Trade name

2G Adhesive Sealer

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture

Adhesive

Uses advised against

No special

1.3. Details of the supplier of the safety data sheet

Company and address

#### **Chemworld ApS**

Knardrupgaards Allé 17

DK-3660 Stenløse

Denmark

Tlf: +45 31186095

Revision

07-02-2022

**SDS Version** 

3.0

Date of previous version

2022-01-17 (2.0)

1.4. Emergency telephone number

Contact The National Poisons Information Service (dial 111, 24 h service).

See section 4 "First aid measures".

## SECTION 2: Hazards identification

## 2.1. Classification of the substance or mixture

Not classified according to Regulation (EC) No. 1272/2008 (CLP)

2.2. Label elements

Hazard pictogram(s)

Not applicable

Signal word

Not applicable

Hazard statement(s)

Not applicable

Safety statement(s)

General

-

Prevention

-

Response

-

Storage

\_

Disposal

\_



#### Hazardous substances

No special

## 2.3. Other hazards

#### Additional labelling

EUH208, Contains Trimethoxyvinylsilane. May produce an allergic reaction.

EUH210, Safety data sheet available on request.

#### Additional warnings

This mixture/product does not contain any substances considered to meet the criteria classifying them as PBT and/or vPvB.

## SECTION 3: Composition/information on ingredients

#### ▼3.2. Mixtures

Product/substance	Identifiers	% w/w	Classification	Note
Trimethoxyvinylsilane	CAS No.: 2768-02-7 EC No.: 220-449-8 REACH: Index No.: 014-049-00-0	<1%	Flam. Liq. 3, H226 Skin Sens. 1B, H317 Acute Tox. 4, H332	
2-methoxy-1-methylethyl acetate	CAS No.: 108-65-6 EC No.: 203-603-9 REACH: Index No.: 607-195-00-7	<1%	Flam. Liq. 3, H226 STOT SE 3, H336	[1]
Methanol (released in small quantities during vulcanisation)	CAS No.: 67-56-1 EC No.: 200-659-6 REACH: Index No.: 603-001-00-X	<0.1%	Flam. Liq. 2, H225 Acute Tox. 3, H301 Acute Tox. 3, H311 Acute Tox. 3, H331 STOT SE 1, H370	[1], [3]

\_\_\_\_

See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available.

### Other information

- [1] European occupational exposure limit
- [3] According to UK REACH, Annex XVII, the substance is subject to restrictions.

## SECTION 4: First aid measures

## 4.1. Description of first aid measures

## General information

In the case of accident: Contact a doctor or casualty department – take the label or this safety data sheet. Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an unconscious person water or other drink.

#### Inhalation

Upon breathing difficulties or irritation of the respiratory tract: Bring the person into fresh air and stay with him/her.

## Skin contact

IF ON SKIN: Wash with plenty of water and soap.

Remove contaminated clothing and shoes. Ensure to wash exposed skin thoroughly with water and soap. DO NOT use solvents or thinners.

If skin irritation occurs: Get medical advice/attention.

2G Adhesive Sealer



#### Eye contact

Upon irritation of the eye: Remove contact lenses and open eyes widely. Flush eyes with water or saline water(20-30°C) for at least 5 minutes. Seek medical assistance and continue flushing during transport.

#### Ingestion

Provide plenty of water for the person to drink and stay with him/her. In case of malaise, seek medical advice immediately and bring the safety data sheet or label from the product. Do not induce vomiting, unless recommended by the doctor. Have the victim lean forward with head down to avoid inhalation of- or choking on vomited material.

#### **Burns**

Not applicable

#### 4.2. Most important symptoms and effects, both acute and delayed

This product contains substances that may trigger an allergic reaction to predisposed persons.

#### 4.3. Indication of any immediate medical attention and special treatment needed

No special

#### Information to medics

Bring this safety data sheet or the label from this product.

## **SECTION 5: Firefighting measures**

#### 5.1. Extinguishing media

Suitable extinguishing media: Alcohol-resistant foam, carbon dioxide, powder, water mist.

Unsuitable extinguishing media: Waterjets should not be used, since they can spread the fire.

## 5.2. Special hazards arising from the substance or mixture

Fire will result in dense smoke. Exposure to combustion products may harm your health. Closed containers, which are exposed to fire, should be cooled with water. Do not allow fire-extinguishing water to enter the sewage system and nearby surface waters.

If the product is exposed to high temperatures, e.g. in the event of fire, dangerous decomposition compounds are produced. These are:

Carbon oxides (CO / CO2).

Some metal oxides.

#### 5.3. Advice for firefighters

Fire fighters should wear appropriate personal protective equipment.

#### SECTION 6: Accidental release measures

## 6.1. Personal precautions, protective equipment and emergency procedures

No specific requirements

#### 6.2. Environmental precautions

Avoid discharge to lakes, streams, sewers, etc.

## 6.3. Methods and material for containment and cleaning up

Use sand, earth, vermiculite, diatomaceous earth to contain and collect non-combustible absorbent materials and place in container for disposal, according to local regulations.

To the extent possible cleaning is performed with normal cleaning agents. Avoid use of solvents.

## 6.4. Reference to other sections

See section 13 on "Disposal considerations" in regard of handling of waste.

See section 8 "Exposure controls/personal protection" for protective measures.

## SECTION 7: Handling and storage

## 7.1. Precautions for safe handling

Smoking, drinking and consumption of food is not allowed in the work area.

See section 8 "Exposure controls/personal protection" for information on personal protection.

#### 7.2. Conditions for safe storage, including any incompatibilities

Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

## Recommended storage material

Always store in containers of the same material as the original container.



## Storage temperature

Dry, cool and well ventilated

## Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

#### 7.3. Specific end use(s)

This product should only be used for applications quoted in section 1.2

#### SECTION 8: Exposure controls/personal protection

## 8.1. Control parameters

Limestone

Long term exposure limit (8 hours) (mg/m³): 10(inhalable)/4(respirable)

Titanium dioxide

Long term exposure limit (8 hours) (mg/m³): 10(inhalable)/4(respirable)

2-methoxy-1-methylethyl acetate

Long term exposure limit (8 hours) (ppm): 50

Long term exposure limit (8 hours) (mg/m³): 274

Short term exposure limit (15 minutes) (ppm): 100

Short term exposure limit (15 minutes) (mg/m³): 548

Annotations:

Sk = Can be absorbed through the skin and lead to systemic toxicity.

Methanol (released in small quantities during vulcanisation)

Long term exposure limit (8 hours) (ppm): 200

Long term exposure limit (8 hours) (mg/m³): 266

Short term exposure limit (15 minutes) (ppm): 250

Short term exposure limit (15 minutes) (mg/m³): 333

Annotations:

Sk = Can be absorbed through the skin and lead to systemic toxicity.

The Control of Substances Hazardous to Health Regulations 2002. SI 2002/2677 The Stationery Office 2002. EH40/2005 Workplace exposure limits (Fourth Edition 2020).

#### **▼** DNEL

Product/substance Limestone
DNEL 6,36 mg/m3
Route of exposure Inhalation

Duration Long term – Local effects - Workers

Product/substance Limestone
DNEL 1,06 mg/m3
Route of exposure Inhalation

Duration Long term – Local effects - General population

Product/substance Limestone
DNEL 6,1 mg/kg bw/day

Route of exposure Oral

Duration Long term – Systemic effects - General population

## PNEC

Product/substance Limestone PNEC 100mg/l

2G Adhesive Sealer Page 4 of 12



Route of exposure

Sewage treatment plant

**Duration of Exposure** 

## 8.2. Exposure controls

Compliance with the given occupational exposure limits values should be controlled on a regular basis.

#### General recommendations

Smoking, drinking and consumption of food is not allowed in the work area.

#### Exposure scenarios

There are no exposure scenarios implemented for this product.

#### **Exposure limits**

Professional users are subjected to the legally set maximum concentrations for occupational exposure. See occupational hygiene limit values above.

#### Appropriate technical measures

The formation of vapours must be kept at a minimum and below current limit values (see above). Installation of a local exhaust system if normal air flow in the work room is not sufficient is recommended. Ensure emergency eyewash and -showers are clearly marked.

#### Hygiene measures

In between use of the product and at the end of the working day all exposed areas of the body must be washed thoroughly. Always wash hands, forearms and face.

## Measures to avoid environmental exposure

No specific requirements

## Individual protection measures, such as personal protective equipment

#### Generally

Use only CE marked protective equipment.

#### Respiratory Equipment

Work situation	Туре	Class	Colour	Standards
If used in small and very badly ventilated rooms (not relevant if the room is well ventilated)	AX	-	Brown	EN14387

## Skin protection

No specific requirements

#### Hand protection

Material	Glove thickness (mm)	Breakthrough time (min.)	Standards	
Nitrile	0.1	> 480	EN374-2, EN388	



#### Eye protection

No specific requirements

## SECTION 9: Physical and chemical properties

## 9.1. Information on basic physical and chemical properties

Physical state

Liquid

Colour

Various colours

## Odour / Odour threshold

Testing not relevant or not possible due to nature of the product.

Testing not relevant or not possible due to nature of the product.

Density (g/cm<sup>3</sup>)

# CHEMWORLD

#### 1.46

#### Kinematic viscosity

Testing not relevant or not possible due to nature of the product.

#### Particle characteristics

Does not apply to liquids.

#### Phase changes

#### Melting point/Freezing point (°C)

Testing not relevant or not possible due to nature of the product.

## Softening point/range (waxes and pastes) (°C)

Does not apply to liquids.

#### Boiling point (°C)

Testing not relevant or not possible due to nature of the product.

#### Vapour pressure

Testing not relevant or not possible due to nature of the product.

#### Relative vapour density

Testing not relevant or not possible due to nature of the product.

#### Decomposition temperature (°C)

Testing not relevant or not possible due to nature of the product.

#### Data on fire and explosion hazards

#### Flash point (°C)

Testing not relevant or not possible due to nature of the product.

#### Ignition (°C)

Testing not relevant or not possible due to nature of the product.

#### Auto flammability (°C)

Testing not relevant or not possible due to nature of the product.

#### Lower and upper explosion limit (% v/v)

Testing not relevant or not possible due to nature of the product.

#### Solubility

## Solubility in water

Testing not relevant or not possible due to nature of the product.

#### n-octanol/water coefficient

Testing not relevant or not possible due to nature of the product.

## Solubility in fat (g/L)

Testing not relevant or not possible due to nature of the product.

#### 9.2. Other information

#### Other physical and chemical parameters

No data available

#### SECTION 10: Stability and reactivity

## 10.1. Reactivity

No data available

## 10.2. Chemical stability

The product is stable under the conditions, noted in section 7 "Handling and storage".

## 10.3. Possibility of hazardous reactions

No special

## 10.4. Conditions to avoid

No special

## 10.5. Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

#### 10.6. Hazardous decomposition products

The product is not degraded when used as specified in section 1.

## SECTION 11: Toxicological information

#### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

2G Adhesive Sealer

According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878

## **▼** Acute toxicity

Product/substance

Limestone

Test method

Result

Species Route of exposure

Rat Inhalation

Test

LC50 >2,61mg/l ·

Other information

Product/substance

Limestone

Test method

Species Rat Route of exposure Oral Test

LD50

Result

>1581mg/l ·

Other information

Product/substance

Test method

Titanium dioxide

Rat Species Route of exposure Oral

LD50 Test >10000 · Result

Other information

Product/substance

Trimethoxyvinylsilane

Test method

Rat **Species** Oral Route of exposure Test LD50

7100 mg/kg · Result

Other information

Product/substance

Test method

Trimethoxyvinylsilane

Species Rabbit Route of exposure Test

Dermal LD50

Result 3200 mg/kg ·

Other information

Product/substance

Trimethoxyvinylsilane

Test method

**Species** Rat Inhalation Route of exposure LD50 Test 16,8 mg/l/4h ·

Result

Other information

## Skin corrosion/irritation

Product/substance

Trimethoxyvinylsilane

Test method

Rabbit **Species** 

2G Adhesive Sealer Page 7 of 12



Duration 96 hours

Result No adverse effect observed (Not irritating)

Other information

## Serious eye damage/irritation

Product/substance Trimethoxyvinylsilane

Test method

Species Rabbit

Duration No data available.

Result Adverse effect observed (Irritating)

Other information

## Respiratory sensitisation

Based on available data, the classification criteria are not met.

## Skin sensitisation

Product/substance Trimethoxyvinylsilane

Test method

Species Guinea pig

Result No adverse effect observed (not sensitising)

Other information

#### Germ cell mutagenicity

Based on available data, the classification criteria are not met.

#### Carcinogenicity

Based on available data, the classification criteria are not met.

## Reproductive toxicity

Based on available data, the classification criteria are not met.

#### STOT-single exposure

Based on available data, the classification criteria are not met.

#### STOT-repeated exposure

Based on available data, the classification criteria are not met.

## Aspiration hazard

Based on available data, the classification criteria are not met.

## 11.2. Information on other hazards

#### Long term effects

No special

## Endocrine disrupting properties

No special

#### Other information

Titanium dioxide has been classified by IARC as a group 2B carcinogen.

#### SECTION 12: Ecological information

#### ▼ 12.1. Toxicity

Product/substance Limestone

Test method

Species Algae

Compartment

 $\begin{array}{ll} \text{Duration} & 72 \text{ hours} \\ \text{Test} & \text{EC50} \\ \text{Result} & >79 \text{mg/l} \cdot \end{array}$ 

Other information

2G Adhesive Sealer Page 8 of 12

According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878

Product/substance

Limestone

Test method

**Species** 

Daphnia

Compartment

Duration 48 hours EC50 Test Result >79mg/l ·

Other information

Product/substance

Limestone

Test method

Species Fish

Compartment

96 hours Duration LC50 Test >79mg/l · Result

Other information

Product/substance

Limestone

Test method **Species** Compartment

Duration 96 hours Test LC50 >876mg/l · Result

Other information

Product/substance

Trimethoxyvinylsilane

Test method

Species Fish

Compartment

Duration 96 hours Test LC50 191 mg/l · Result

Other information

Product/substance Test method

Trimethoxyvinylsilane

Daphnia Species

Compartment

48 hours Duration EC50 Test 169 mg/l · Result

Other information

Product/substance

Trimethoxyvinylsilane

Test method

Species Daphnia

Compartment

21 days Duration Test NOEC 25 mg/l · Result

Other information

2G Adhesive Sealer Page 9 of 12 Trimethoxyvinylsilane



Product/substance

Test method

Species Algae

Compartment

 $\begin{array}{ll} \text{Duration} & 72 \text{ hours} \\ \text{Test} & \text{NOEC} \\ \text{Result} & 25 \text{ mg/l} \cdot \end{array}$ 

Other information

## 12.2. Persistence and degradability

Product/substance Titanium dioxide

Biodegradable Test method

Result

Product/substance Trimethoxyvinylsilane

Biodegradable Test method

No

No

#### 12.3. Bioaccumulative potential

No data available

#### 12.4. Mobility in soil

Result

No data available

## 12.5. Results of PBT and vPvB assessment

This mixture/product does not contain any substances considered to meet the criteria classifying them as PBT and/or vPvB.

## 12.6. Endocrine disrupting properties

No special

#### 12.7. Other adverse effects

No special

#### **SECTION 13: Disposal considerations**

#### 13.1. Waste treatment methods

Product is not covered by regulations on dangerous waste.

Regulation (EU) No 1357/2014 of 18 December 2014 on waste.

## EWC code

08 04 10 Waste adhesives and sealants other than those mentioned in 08 04 09

## Specific labelling

Not applicable

## Contaminated packing

Packaging containing residues of the product must be disposed of similarly to the product.

#### **SECTION 14: Transport information**

## 14.1. - 14.4.

Not dangerous goods according to ADR, IATA and IMDG.

## ADR/RID

Not applicable

#### **IMDG**

Not applicable

## MARINE POLLUTANT

No

2G Adhesive Sealer Page 10 of 12

# CHEMWORLD

#### IATA

Not applicable

## 14.5. Environmental hazards

Not applicable

#### 14.6. Special precautions for user

Not applicable

## 14.7. Maritime transport in bulk according to IMO instruments

No data available

## **SECTION 15: Regulatory information**

# 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture Restrictions for application

No special

#### Demands for specific education

No specific requirements

#### SEVESO - Categories / dangerous substances

Methanol (released in small quantities during vulcanisation)

#### Additional information

Not applicable

#### **▼** Sources

Control of Major Accident Hazards (COMAH) Regulations 2015.

Regulation (EU) No 1357/2014 of 18 December 2014 on waste.

CLP Regulation (EC) No 1272/2008, as retained and amended in UK law.

EC-Regulation 1907/2006 (REACH), as amended by UK REACH Regulations SI 2019/758

#### 15.2. Chemical safety assessment

No

#### SECTION 16: Other information

## ▼ Full text of H-phrases as mentioned in section 3

H225, Highly flammable liquid and vapour.

H226, Flammable liquid and vapour.

H301, Toxic if swallowed.

H311, Toxic in contact with skin.

H317, May cause an allergic skin reaction.

H331, Toxic if inhaled.

H332, Harmful if inhaled.

H336, May cause drowsiness or dizziness.

H370, Causes damage to organs.

#### Abbreviations and acronyms

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway

ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road

ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

CAS = Chemical Abstracts Service

CE = Conformité Européenne

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]

CSA = Chemical Safety Assessment

CSR = Chemical Safety Report

DMEL = Derived Minimal Effect Level

DNEL = Derived No Effect Level

EINECS = European Inventory of Existing Commercial chemical Substances

ES = Exposure Scenario

EUH statement = CLP-specific Hazard statement

EWC = European Waste Catalogue



GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IARC = International Agency for Research on Cancer (IARC)

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)

OECD = Organisation for Economic Co-operation and Development

PBT = Persistent, Bioaccumulative and Toxic

PNEC = Predicted No Effect Concentration

RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail

RRN = REACH Registration Number

SCL = A specific concentration limit.

SVHC = Substances of Very High Concern

STOT-RE = Specific Target Organ Toxicity - Repeated Exposure

STOT-SE = Specific Target Organ Toxicity - Single Exposure

TWA = Time weighted average

**UN = United Nations** 

UVCB = Complex hydrocarbon substance

VOC = Volatile Organic Compound

vPvB = Very Persistent and Very Bioaccumulative

## Additional information

Not applicable

▼ The safety data sheet is validated by

ESC

#### Other

A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a blue triangle.

The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.

It is recommended to hand over this safety data sheet to the actual user of the product. Information in this safety data sheet cannot be used as a product specification.

Country-language: GB-en

2G Adhesive Sealer Page 12 of 12